

TORQUE SPECIFICATION

Part Tightened	N·m	kgf·cm	ft·lbf
Bleeder plug	8.3	85	73 in·lbf
Brake master cylinder x Piston stopper bolt	10	102	7
Brake master cylinder union x Brake master cylinder	1.7	17.5	15.2 in·lbf
Brake master cylinder sub-assy x Brake booster assy	13	128	9
Brake tube x Brake master cylinder sub-assy	15	153	11
Brake master cylinder reservoir sub-assy x Body	8.8	90	78 in·lbf
Brake booster push rod clevis lock nut	26	265	19
Vacuum warning switch assy x Brake booster assy	14	140	10
Brake booster assy x Body	13	130	9
Pressure feed tube assy x Vane pump assy	52	525	38
Pressure feed tube clamp	7.8	80	69 in·lbf
Brake actuator assy x Bracket	5.4	55	48 in·lbf
Brake actuator w/ bracket x Body	19	194	14
Power steering tube clamp x Body	7.8	80	69 in·lbf
Brake tube x Brake actuator assy	15	153	11
ABS & TRACTION actuator assy x Bracket	5.4	55	48 in·lbf
ABS & TRACTION actuator w/ bracket x Body	19	194	14
Power steering tube clamp x Body	7.8	80	69 in·lbf
Brake tube x ABS & TRACTION actuator assy	15	153	11
Yawrate sensor x Body	13	136	10