

TORQUE SPECIFICATION

Part Tightened	N·m	kgf·cm	ft·lbf
Filler and drain plugs	49	500	36
Floor shift shift lever Assy x Body	12	120	9
Floor shift transmission control cable Assy x Body	5.0	51	44 in.·lbf
Engine hanger x Engine 1AZ-FE Engine Type	38	387	28
Engine hanger x Engine 1CD-FTV Engine Type	36.8	375	27
Transaxle x Engine 1AZ-FE Engine Type			
Bolt A:	64	650	47
Bolt B:	46	470	34
Bolt C:	44	449	32
Transaxle x Engine 1CD-FTV Engine Type			
Bolt A:	64	650	47
Bolt B:	46	470	34
Bolt C:	40	409	30
Bolt D:	19.5	199	14
Bolt E:	8.0	82	71 in.·lbf
Engine mounting bracket RR x Transaxle	64	652	47
Engine mounting bracket FR x Transaxle	64	652	47
Center member x Body Bolt A:	45	459	33
Bolt B:	80	816	59
Engine mounting insulator RR x Engine mounting bracket RR	87	887	64
Hose clamp x Engine mounting insulator RR	7.8	80	69
Engine mounting insulator RR x Suspension member	80	816	59
Engine mounting bracket LH x Transaxle	64	653	47
Engine mounting insulator LH x Body Bolt A:	52	530	38
Nut B:	56	571	41
Engine mounting insulator FR x Engine mounting bracket FR	56	571	41
Transmission case protector x Transaxle	18	184	13
Floor shift transmission control cable Assy x Transaxle	17	173	13
Clutch release cylinder Assy x Transaxle 1AZ-FE Engine Type			
Bolt A:	12	120	9
Bolt B:	25	255	18
Bolt C:	5.0	51	44 in.·lbf
Bolt D:	11.8	120	9
Wire harness x Transaxle	10	102	7
Starter x Transaxle	37	377	27
Starter wire x Starter	9.8	100	87 in.·lbf
Flexible hose tube x Transaxle 1CD-FTV Engine Type	12	122	9
Air cleaner Assy x Body	5.0	50	44 in.·lbf
Engine cover x Engine 1AZ-FE Engine Type	7.0	71	62 in.·lbf