

# ENGINE HOOD/DOOR

## TORQUE SPECIFICATION

0309Y-01

Part Tightened	N·m	kgf·cm	ft·lbf
HOOD	—	—	—
Hood × Hood hinge	11.5	117	8.5
Hood lock × Body	7.0	71	62 in.·lbf
FRONT DOOR	—	—	—
Door lock × Door panel Screw:	5.0	51	45 in.·lbf
Door lock × Door panel Bolt:	8.0	82	71 in.·lbf
Window regulator × Door panel	8.0	82	71 in.·lbf
Door glass × Window regulator	7.0	72	62 in.·lbf
Door hinge × Door panel Upper Side:	26	265	19
Door hinge × Door panel Lower Side:	26	265	19
Door lock striker × Body	23	235	17
REAR DOOR	—	—	—
Door lock × Door panel Screw:	5.0	51	45 in.·lbf
Door lock × Door panel Bolt:	8.0	82	71 in.·lbf
Door glass × Window regulator	7.0	71	62 in.·lbf
Window regulator × Door panel	8.0	82	71 in.·lbf
Door hinge × Door panel Upper Side:	26	265	19
Door hinge × Door panel Lower Side:	26	265	19
Door lock striker × Body	23	235	17
BACK DOOR	—	—	—
Door lock × Door panel	15	153	11
Back door × Hinge	19	194	14
Door lock striker × Body	17.5	179	13
BACK DOOR STAY	—	—	—
Back door Stay × Body	7.5	77	66 in.·lbf