

PROPELLER SHAFT

SERVICE DATA

SS07Q-01

Propeller shaft runout	Max.	0.8 mm (0.031 in.)
Spider bearing axial play		0.05 mm (0.0020 in.)
Spider bearing selection	Mark	
Bearing cup outer diameter	None	29.008 - 29.021 mm (1.1420 - 1.1426 in.)
	Red	29.028 - 29.041 mm (1.1428 - 1.1433 in.)
Bearing hole inner diameter	None	29.000 - 29.020 mm (1.1417 - 1.1425 in.)
	Drill	29.021 - 29.042 mm (1.1426 - 1.1434 in.)
Snap ring thickness	Mark or Color	
	1	2.100 - 2.150 mm (0.0827 - 0.0846 in.)
	2	2.150 - 2.200 mm (0.0846 - 0.0866 in.)
	3	2.200 - 2.250 mm (0.0866 - 0.0886 in.)
	Brown	2.250 - 2.300 mm (0.0886 - 0.0906 in.)
	Blue	2.300 - 2.350 mm (0.0906 - 0.0925 in.)
	6	2.350 - 2.400 mm (0.0925 - 0.0945 in.)
	7	2.400 - 2.450 mm (0.0945 - 0.0965 in.)
	8	2.450 - 2.500 mm (0.0965 - 0.0984 in.)