

TORQUE SPECIFICATION

Part Tightened	N·m	kgf·cm	ft·lbf
Brake line union nut	15	155	11
Bleeder plug	8.4	86	74 in.·lbf
Brake booster clevis lock nut	26	265	19
Stop lamp lock nut	26	265	19
Brake stroke sensor assy set bolt	9.3	95	82 in.·lbf
Brake pedal sub-assy set bolt	37	375	27
Brake pedal support assy x Body	13	130	9
Brake pedal support assy x Reinforcement	24	241	18
Brake master cylinder union No.1 set screw	1.8	18	16 in.·lbf
Brake master cylinder x Bracket	13	127	9
Brake actuator bracket x Tube bracket	5.0	51	44 in.·lbf
Cowl top panel sub-assy outer front	6.4	65	57 in.·lbf
Engine room R/B No.2 x Body	8.4	86	74 in.·lbf
Brake stroke simulator stud bolt	5.0	51	44 in.·lbf
Brake stroke simulator x Bracket	6.0	61	53 in.·lbf
Brake stroke simulator Bracket x Body	8.5	87	75 in.·lbf
Brake stroke simulator x Brake actuator tube assy	8.5	87	75 in.·lbf
Wheel nut	103	1,050	76
Front brake cylinder mounting x Steering knuckle	109	1,114	81
Front brake cylinder x Front brake cylinder mounting	34	347	25
Front brake cylinder x Flexible hose	33	337	24
Rear drum brake wheel cylinder x Backing plate	9.8	100	87 in.·lbf
Brake actuator assy x Brake actuator bracket No.2	18	184	13
Brake actuator assy x Gusset assy	7.5	76	66 in.·lbf
Brake actuator assy x Bracket	18	184	13
Brake actuator assy x Brake actuator damper	18	184	13
Brake actuator w/ gusset assy x Body	20	200	15
Brake actuator assy x Brake tube clamp bracket	5.0	51	44
Brake actuator x Brake actuator tube assy	8.5	87	75 in.·lbf
Brake actuator bracket x Front brake tube No.5 bracket	5.0	51	44 in.·lbf
Front speed sensor x Steering knuckle	8.0	82	71 in.·lbf
Front speed sensor wire harness clamp x Body Bolt A:	8.0	82	71 in.·lbf
Front speed sensor wire harness clamp x Shock absorber Bolt B:	19	192	14
Skid control ECU assy x Body	5.0	51	44 in.·lbf
Brake control power supply assy x Body	19	194	14
Yawrate sensor x Body	19	194	14