

COOLING

SERVICE DATA

031LQ-02

| | | |
|---------------------------|-----------------------------|---|
| Thermostat | | |
| Valve opening temperature | | 80 to 84°C (176 to 183°F) |
| Valve lift | at 95°C (205°F) | 8.5 mm (0.335 in.) or more |
| Radiator cap sub-assy | | |
| Standard opening pressure | | 74 to 103 kPa (0.75 to 1.05 kgf/cm ² , 10.7 to 14.9 psi) |
| Minimum opening pressure | | 59 kPa (0.6 kgf/cm ² , 8.5 psi) |
| Cooling fan | | |
| Standard amperage | | 9.2 to 11.0 A |
| Cooling fan relay | | |
| Specified condition | Between terminals 3 and 5 | 10 kΩ or higher |
| | Between terminals 3 and 5 | Below 1 Ω (Apply battery voltage to terminals 1 and 2) |
| Cooling fan relay No.2 | | |
| Specified condition | Between terminals 3 and 4 | Below 1 Ω |
| | Between terminals 3 and 5 | 10 kΩ or higher |
| | Between terminals 3 and 5 | Below 1 Ω (Apply battery voltage to terminals 1 and 2) |
| Integration relay | | |
| Specified condition | Between terminals B1 and B4 | 10 kΩ or higher |
| | Between terminals B1 and B4 | Below 1 Ω (Apply battery voltage to terminals 1 and 2) |