



TERMINALS OF ECU



N

F44303

Symbols (Terminals No.)	Wiring Color	Terminal Description	Condition	Specified Condition
PIG (P7-1) - PGND (P7-2)	W - W-B	EPS fuse	Always	10 to 16 V
PGND (P7-2) - Body ground	W-B - Body ground	Body ground	Always	Below 1 Ω
M1 (P9-1) - PGND (P7-2)	R - W-B	Power steering motor	<ul style="list-style-type: none"> • With power switch on (IG), turn the steering wheel to left • With power switch on (IG), turn the steering wheel to right 	Below 1 V 10 to 16 V
M2 (P9-2) - PGND (P7-2)	B - W-B	Power steering motor	<ul style="list-style-type: none"> • With power switch on (IG), turn the steering wheel to left • With power switch on (IG), turn the steering wheel to right 	10 to 16 V Below 1 V
CANH (P8-1) - CANL (P8-7)	B - W	CAN BUS	Power switch is off	108 to 132 Ω
SIL (P8-2) - PGND (P7-2)	W - W-B	DLC3	Communication is established by connecting the intelligent tester II to the DLC3	Pulse generation (See waveform 1)
IG (P8-6) - PGND (P7-2)	B - W-B	ECU-IG fuse	Power switch is on (IG)	10 to 16 V
TRQ1 (P10-5) - PGND (P7-2)	B - W-B	Torque sensor	With power switch on (IG), turn the steering wheel to left and right	0.3 to 4.7 V
TRQV (P10-6) - PGND (P7-2)	Y - W-B	Torque sensor	Power switch is on (IG)	7.5 to 8.5 V
TRQ2 (P10-7) - PGND (P7-2)	R - W-B	Torque sensor	With power switch on (IG), turn the steering wheel to left and right	0.3 to 4.7 V
TRQG (P10-8) - PGND (P7-2)	W - W-B	Torque sensor	Always	Below 1 Ω



Waveform 1

Reference:

Terminal	SIL - Body ground
Tool setting	5 V/DIV, 1 ms/DIV
Condition	Communication is established by connecting the intelligent tester II to the DLC3