



Technical Service BULLETIN

October 1, 1999

Title:

TIRE INFLATION & WHEEL LUG TORQUE REFERENCE CHART

Models:

All '00 Models

PG031-99

PRODUCT GENERAL INFORMATION

Introduction Proper tire inflation is important to **maximize tire life** and **vehicle ride comfort**. 2000 MY Toyota vehicles are available with a wide variety of wheel sizes and tire profiles. **Prior to customer vehicle delivery**, refer to the following table to identify the appropriate tire pressure setting. Adjust tire pressures accordingly.

Applicable Vehicles • All 2000 Models

**Tire Pressure
Settings**

MODEL	TIRE SIZE	TIRE PRESSURE COLD		WHEEL NUT TORQUE (ft-lbf)
		FRONT (psi)	REAR (psi)	
Tundra	P245/70R16 106S	26	35	83
	P265/70R16 111S	26	29	83
Tacoma	P195/75R14 92S	29	35	83
	P215/70R14 96S	29	29	83
	P225/75R15 102S	26	29	83
	P265/75R15 112S	26	26	83
	31X10.5R15LT C	26	29	83
Tacoma PreRunner	P225/75R15 102S	26	29	83
	P265/75R15 112S	26	26	83
	31X10.5R15LT C	26	29	83
Land Cruiser	P275/70R16 114S	29/29*	32/35*	97
4Runner	P225/75R15 102S	29	29	83
	P265/70R16 111S	32	32	83
RAV4 2 Door	P215/70R16 99S	26	26	76
	P235/60R16 100H	25	25	76
RAV4 4 Door	P215/70R16 99S	28	26	76
	P235/60R16 100H	25	25	76
Sienna	P205/70R15 95S	35	35	76
	P215/65R15 95S	32/35*	32/35*	76

* Recommended tire inflation pressure under high load capacity.



Toyota Supports ASE Certification

Index # 052476

**Tire Pressure
Settings**
(Continued)

MODEL	TIRE SIZE	TIRE PRESSURE COLD		WHEEL NUT TORQUE (ft-lbf)
		FRONT (psi)	REAR (psi)	
ECHO	155/80R13 79S	32	32	76
	P175/65R14 81S	32	32	76
Corolla	P175/65R14 81S	30	30	76
	P185/65R14 85S	30	30	76
Celica 2ZZ-GE	P205/55R15 87V	32	32	76
	205/50R16 87V	32	32	76
Celica 1ZZ-FE	195/60R15 88H	29	29	76
	P195/60R15 87H	29	29	76
Camry	P195/70R14 90S	30	30	76
	P205/65R15 92H	32*/29**/32***	32*/29**/32***	76
	P205/60R16 91H	32	32	76
Camry Solara	P205/65R15 92H	29	29	76
	P205/60R16 91H	32	32	76
Avalon	P205/65R15 92H	31	31	76
	P205/60R16 91H	32	32	76

* For vehicle capacity weight.

** For reduced loads (1 to 4 passengers).

*** For trailer towing.