



































		1CD-FTV
cm ³ or CC (cu. in.)		1995 (121.7)
		
		10.5–12.5 (0.41–0.49) ※196–392 (20–40)
mm (in.) N (kgf)		14–17 (0.55–0.67) ※294–441 (30–45)
	20°C (68°F)	1.1
Ω		
	28°C (82°F)	0.4
secs		
		0.20–0.30 (0.008–0.012)
mm (in.)		0.35–0.45 (0.014–0.018)
		750–850
rpm		5100–5250

		2628 (26.8, 381)
		2157 (22.0, 313)
		490 (5.0, 71)
	A	 ① 45 (460, 33) ③ 90° ② 90° ④ 90°
	B	20.5 (209, 15)
	C	46.5 (474, 34)
	D	25.7 (262, 19)
	E	New *31 (316, 23) Reuse *36 (371, 27) 34 (347, 25) 46 (469, 33.9)
		29 (0.3, 4.2)
	4500 rpm	245–588 (2.5–6.0, 36–85)

		CDE
		5.3 (5.6, 4.7)
		5.9 (6.2, 5.2)
		ACEA B1, API CF-4 or CF (You may also use API CE or CD.)
		7.4 (7.8, 6.5)

Corolla Verso Diesel



	A	151–161 (5.945–6.339)	155.4–165.4 (6.118–6.512)
	B	5–15 (0.197–0.591)	
	C	25 (0.98)	
mm (in.)		SAE J1704 or FMVSS No. 116 DOT4	

	A	145.1–155.1 (5.713–6.106)	139.5–149.5 (5.492–5.886)
	B	1–6 (0.04–0.24)	
	C*1	50 (2.0)	50 (2.0)
mm (in.)		SAE J1704 or FMVSS No. 116 DOT4	

196 N (20 kgf, 44.1 lbf)			
	6–9		

	A	2.0 (0.079)	
mm (in.)	B	24.0 (0.945)	8.5 (0.335)

	1.6 (0.063)
--	-------------

	181.0 (7.126)
--	---------------

	CDE
	294 (2998, 217)
N·m (kgf-cm, ft-lbf)	

	103 (10.5, 76)
N·m (kgf-m, ft-lbf)	

	CDE
	2.5 (2.6, 2.2)
liter (US qts, Imp. qts)	
	API GL-4 or GL-5 SAE 75W-90

	CDE
	30 (1.2)
mm (in.)	

	A	–0°32'±45' (–0.53°±0.75°)	–1°27'±45' (–1.45°±0.75°)
	B	12°17'±45' (12.28°±0.75°)	—
	C	2°53'±45' (2.88°±0.75°)	—
	D	35°25'±2° (35.41°±2°)	—
	E+F	0°10'±12' (0.16°±0.2°)	0°11'±12' (0.18°±0.2°)
	G–H mm (in.)	2±2 (0.08±0.08)	2.2±2.5 (0.09±0.1)

	km/h (mph)			
	160 (100)	260*2 *3 (2.6, 37)	240*2 (2.4, 35)	280*3 (2.8, 41)
	160 (100)	240*2 *3 (2.4, 35)	240*2 *3 (2.4, 35)	
kPa (kgf/cm ² or bar, psi)	205/55 R16 91V			